


**Jacox, M. G., Watts, K. D., "INEL XPS Report", Idaho
National Engineering Laboratory, EG&G Idaho, Inc.,
Idaho Falls, Idaho, 83415, November 1993**

THIS PAGE BLANK (USPTO)

All Data Displayed (No Peak Plotting)



C:\MASSEMOODATA\111893A.DAT


Record: 1

08:28:08 11/18/1993 08:31:32

C:\MASSEMOODATA\111893B.DAT

Record: 1

08:57:30 11/18/1993 08:37:39



Cursor


1445

28173 Counts/Sec


Counts

54.700


3 Energy (eV)




ESCA MULTIPLEX 11/24/93 EL= REG 2 ANGLE= 15 deg ACO TIME=114.08 min
FILE: Nitest50 Ni wire treated overnight at IRC.
SCALE FACTOR= 0.116 k c/s, OFFSET= 1.036 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/22/93 EL= REG 2 ANGLE= 15 deg ACO TIME=96.53 min
FILE: Nitest32 2nd Ni wire treated prior to IRC.
SCALE FACTOR= 0.274 k c/s, OFFSET= 1.580 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=76.05 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 3.401 k c/s, OFFSET= 9.545 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACO TIME=84.83 min
FILE: Nitest25 Ni foil treated in lab for 24 hr. As received.
SCALE FACTOR= 1.920 k c/s, OFFSET= 8.515 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min


FILE: Nitest20 Ni wire processed in lab. as received.

SCALE FACTOR= 0.331 k c/s, OFFSET= 2.436 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACO TIME=61.43 min
FILE: Nitest27 Ni wire untreated (base line) using Al X-Ray's.
SCALE FACTOR= 0.326 k c/s, OFFSET= 1.491 k c/s PASS ENERGY=143.050 eV Al 400 W





Several examples of different energy holes effecting shrinkage and the corresponding effective nuclear charges, total energy released, and final radii of the orbitspheres going from infinity to the final radius, $a_0/(m + 1)$ are given in Table 20.1.


Table 20.1. Radii, energies, energy holes, and energy released for several states of hydrogen or deuterium.

n	R	V(eV)	T(eV)	Z _{eff}	energy hole (eV)	total energy released (eV) r = ∞ to r = R
-	a_0	-27.2	13.6	1	-	13.6
1	$a_0/2$	-108.8	54.4	2	27.2	54.4
2	$a_0/3$	-244.9	122.4	3	54.4	122.4
3	$a_0/4$	-435.4	217.7	4	81.6	217.7
4	$a_0/5$	-680.2	340.1	5	108.8	340.1
5	$a_0/6$	-979.6	489.6	6	136.1	489.6
6	$a_0/7$	-1333.3	666.4	7	163.3	666.4
7	$a_0/8$	-1741.4	870.4	8	190.5	870.4
8	$a_0/9$	-2204.0	1101.6	9	217.7	1101.6
9	$a_0/10$	-2721.0	1360.5	10	244.9	1360.5

Energy released for any transition is given by $\Delta E_{\text{final}} (\infty \text{ to } R) - \Delta E_{\text{initial}} (\infty \text{ to } R)$

The size of the electron orbitsphere as a function of potential energy is given in Figure 20.2.

Figure 20.2. Quantized sizes and energies of hydrogen and deuterium atoms.





CAF

The electric field E_n , where n is the principal quantum number (1.6). Thus smaller electric field separation for example muon to electron orders of magnitude. 27.21 eV, separation internuclear process is

It is possible for protons, it is about 50% the nuclear Coulombic process.


Hydrogen ground state proton. In photons






AES SURVEY V/F 11/29/93 AREA 1 ACO TIME=13.34 MIN.

FILE: Nitest104 Ni wire treated for 24 Hr at the IRC.

SCALE FACTOR= 47.398 k c/s, OFFSET= 118.853 k c/s BV=5.00kV BI=0.2793uA








AES SURVEY V/F 11/29/93 AREA 1 ACO TIME=6.67 MIN.

FILE: Nitest103 Ni wire treated for 24 Hr at the IRC.

SCALE FACTOR= 35.917 k c/s, OFFSET= 331.575 k c/s BV=5.00kV BI=0.2793uA



30-Nov-1993 09:39:41

Ni-AR-1

Zaster

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION ± SIGMA	K-RATIO**
Al KA	1.89	4.00	0.09	0.0059
Si KA	0.69	1.41	0.07	0.0029
Mn KA	0.08	0.08	0.02	0.0009
Fe KA	0.10	0.10	0.02	0.0013
Ni KA	97.24	94.41	0.42	0.9699
TOTAL	100.00			

ITERATIONS 6

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: K-RATIO = K-RATIO x R
where R = reference(standard)/reference(sample)

NORMALIZATION FACTOR: 1.000

30-Nov-1993 09:41:17

Ni-AR-2

spot

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	2.22	4.66	0.10	0.0070
Si KA	0.80	1.62	0.07	0.0034
Mn KA	0.05	0.05	0.02	0.0006
Fe KA	0.05	0.05	0.02	0.0007
Ni KA	96.88	93.61	0.45	0.9660
TOTAL	100.00			

ITERATIONS 6

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: $K-RATIO = K-RATIO \times R$
where $R = \text{reference(standard)}/\text{reference(sample)}$

NORMALIZATION FACTOR: 1.000

30-Nov-1993 09:47:39

Ni-AR-4

Raster

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	4.11	8.52	0.10	0.0130
Mn KA	0.09	0.09	0.02	0.0011
Fe KA	0.07	0.07	0.02	0.0010
Ni KA	95.73	91.31	0.39	0.9535

TOTAL 100.00

ITERATIONS 7

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: $K-RATIO = K-RATIO \times R$
where $R = reference(standard)/reference(sample)$

NORMALIZATION FACTOR: 1.000

30-Nov-1993 09:42:46

Ni-AR-3

Sp. +

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	3.17	6.61	0.12	0.0100
Si KA	0.71	1.42	0.06	0.0030
Mn KA	0.05	0.05	0.01	0.0005
Fe KA	0.08	0.08	0.02	0.0010
Ni KA	95.99	91.85	0.44	0.9561
TOTAL	100.00			

ITERATIONS 7

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: $K-RATIO = K-RATIO \times R$
where $R = \text{reference(standard)} / \text{reference(sample)}$

NORMALIZATION FACTOR: 1.000

30-Nov-1993 09:57:31

Ni-T-2

5, 2, 1

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	3.80	7.90	0.12	0.0120
K KA	0.34	0.49	0.04	0.0029
Mn KA	0.04	0.04	0.01	0.0005
Fe KA	0.06	0.06	0.02	0.0008
Ni KA	95.75	91.50	0.43	0.9537

TOTAL 99.99

ITERATIONS 6

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: K-RATIO = K-RATIO x R
where R = reference(standard)/reference(sample)

NORMALIZATION FACTOR: 1.000

30-Nov-1993 09:54:39

Ni-T-1

Roster

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

Only ~1/2 - 2%
probably

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	6.47	13.07	0.16	0.0208
K KA	0.35	0.48	0.04	0.0030
Mn KA	0.08	0.08	0.02	0.0009
Fe KA	0.06	0.06	0.02	0.0008
Ni KA	93.04	86.32	0.39	0.9247
TOTAL	100.00			

ITERATIONS 7

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: $K-RATIO = K-RATIO \times R$
where $R = \text{reference(standard)}/\text{reference(sample)}$

NORMALIZATION FACTOR: 1.000

30-Nov-1993 10:00:28

Ni-T-3

Spot

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)

*Only ~1% - 2%
probably*

ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	6.00	12.18	0.17	0.0193
K KA	0.38	0.53	0.04	0.0032
Mn KA	0.08	0.08	0.02	0.0009
Fe KA	0.07	0.06	0.02	0.0009
Ni KA	93.47	87.14	0.41	0.9293
TOTAL	100.00			

ITERATIONS 7

*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: K-RATIO = K-RATIO x R
where R = reference(standard)/reference(sample)

NORMALIZATION FACTOR: 1.000

30-Nov-1993 10:02:41

Ni-T-4

205 to

Accelerating voltage 20.0 KeV
Beam - sample incidence angle 90.0 degrees
Xray emergence angle 35.0 degrees
Xray - window incidence angle 0.0 degrees

STANDARDLESS EDS ANALYSIS
(ZAF CORRECTIONS VIA MAGIC V)


ELEMENT & LINE	WEIGHT PERCENT	ATOMIC PERCENT*	PRECISION 2 SIGMA	K-RATIO**
Al KA	1.46	3.12	0.09	0.0045
K KA	0.25	0.36	0.03	0.0021
Mn KA	0.09	0.09	0.02	0.0010
Fe KA	0.09	0.09	0.02	0.0012
Ni KA	98.11	96.33	0.42	0.9795
TOTAL	100.00			

ITERATIONS 6


*NOTE: ATOMIC PERCENT is normalized to 100

**NOTE: $K-RATIO = K-RATIO \times R$
where $R = \text{reference(standard)}/\text{reference(sample)}$

NORMALIZATION FACTOR: 1.000




ESCA MULTIPLEX 11/19/93 EL=C1 REG 1 ANGLE= 15 deg ACQ TIME=4.19 min
FILE: Nitest27 Ni wire untreated (base line) using Al X-Ray's.
SCALE FACTOR= 0.928 k c/s, OFFSET= 5.646 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/29/93 EL=Fe1 REG 1 ANGLE= 15 deg ACO TIME=116.96 min


FILE: Nitest55 More Fe spectra of Ni wire treated overnight at the IRC

SCALE FACTOR= 0.134 k c/s, OFFSET= 9.937 k c/s PASS ENERGY=143.050 eV Mg 300 W





ESCA SURVEY 11/24/93 ANGLE= 15 deg ACQ TIME=29.36 min
FILE: Nitest51 Ni wire treated overnight at IRC.
SCALE FACTOR= 7.011 k c/s, OFFSET= 0.979 k c/s PASS ENERGY=178.950 eV Al 400 W






1991-05-28 15:01:42 242P.04.05







ESCA SURVEY 11/29/93 ANGLE= 15 deg ACQ TIME=29.36 min
FILE: Nitest56 Ni wire treated over Thanksgiving weekend.
SCALE FACTOR= 4.822 k c/s, OFFSET= 0.306 k c/s PASS ENERGY=178.950 eV Mg 300 W




ESCA MULTIPLEX 11/24/93 EL= REG 2 ANGLE= 15 deg ACO TIME=114.08 min
FILE: Nitest50 Ni wire treated overnight at IRC.
SCALE FACTOR= 0.095 k c/s, OFFSET= 1.036 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/24/93 EL=C1 REG 1 ANGLE= 15 deg ACO TIME=7.54 min
FILE: Nitest50 Ni wire treated overnight at IRC.
SCALE FACTOR= 0.569 k c/s, OFFSET= 3.655 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACO TIME=61.43 min
FILE: Nitest27 Ni wire untreated (base line) using Al X-Ray's.
SCALE FACTOR= 0.307 k c/s, OFFSET= 1.683 k c/s PASS ENERGY=143.050 eV Al 400 W





SPACE and ADVANCED PROGRAMS UNIT
P. O. BOX 1625
IDAHO FALLS ID 83415

To: Mike Hawkins

Company/Org: _____

Fax No: _____

Verify No: _____

From: Mike Jacob

Company/Org: _____


Phone No: _____

Fax No: 1-208-526-2061 (FTS) 8-208-526-2061


No. of pages including the cover page: 2

Note:

Figure 4A




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min
FILE: Nitest20 Ni wire processed in lab. as received.
SCALE FACTOR= 0.331 k c/s, OFFSET= 2.436 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/24/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=114.08 min

FILE: Nitest50 Ni wire treated overnight at IRC.

SCALE FACTOR= 0.116 k c/s, OFFSET= 1.036 k c/s PASS ENERGY=143.050 eV Al 400 W




Cursor

1445

Counts 28173 Counts/Sec

54.700

a Energy (eV)








Figure 4


ESCA SURVEY 11/23/93 ANGLE= 15 deg ACQ TIME=29.36 min
FILE: Nitest40 Ni foil after treatment for 5 days.
SCALE FACTOR= 9.221 k c/s, OFFSET= 0.532 k c/s PASS ENERGY=178.950 eV Al 400 W




ESCA MULTIPLEX 11/23/93 EL=C1 REG 1 ANGLE= 15 deg ACQ TIME=2.51 min
FILE: Nitest41 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.905 k c/s, OFFSET= 1.883 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/23/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=114.08 min
FILE: Nitest41 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.029 k c/s, OFFSET= 0.855 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/23/93 EL= REG 2 ANGLE= 15 deg ACO TIME=114.08 min
FILE: Nitest41 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.039 k c/s, OFFSET= 0.755 k c/s PASS ENERGY=143.050 eV Al 400 W




Cursor

Counts 18374


Counts/Sec 942

46.700


Energy (eV)




ESCA MULTIPLEX 11/23/93 EL=C1 REG 1 ANGLE= 15 deg ACO TIME=4.19 min
FILE: Nitest42 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.378 k c/s, OFFSET= 0.689 k c/s PASS ENERGY= 71.550 eV Al 400 W



ESCA MULTIPLEX 11/23/93 EL= REG 2 ANGLE= 15 deg ACO TIME=609.86 min
FILE: Nitest42 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.012 k c/s, OFFSET= 0.455 k c/s PASS ENERGY= 71.550 eV Al 400 W



ESCA MULTIPLEX 11/23/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=609.86 min
FILE: Nitest42 Ni foil after treatment for 5 days.
SCALE FACTOR= 0.012 k c/s, OFFSET= 0.403 k c/s PASS ENERGY= 71.550 eV Al 400 W




Cursor

486


Counts 50692 Counts/Sec

46.800


a Energy (eV)




ESCA SURVEY 11/22/93 ANGLE= 15 deg ACQ TIME=29.36 min
 FILE: Nitest31 Ni foil treated for 4 days (same foil as 24 hr treat.)
 SCALE FACTOR= 44.544 k c/s, OFFSET= 4.987 k c/s PASS ENERGY=178.950 eV Al 400 W




ESCA MULTIPLEX 11/22/93 EL=C1 REG 1 ANGLE= 15 deg ACQ TIME=1.67 min
FILE: Nitest30 Ni foil treated for 4 days (same foil as 24 hr treat.)
SCALE FACTOR= 4.250 k c/s, OFFSET= 25.454 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/22/93 EL= REG 2 ANGLE= 15 deg ACO TIME=46.80 min
FILE: Nitest30 Ni foil treated for 4 days (same foil as 24 hr treat.)
SCALE FACTOR= 1.109 k c/s, OFFSET= 7.432 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA SURVEY 11/19/93 ANGLE= 15 deg ACQ TIME=29.36 min
 FILE: Nitest26 Ni foil treated in lab for 24 hr. As received.
 SCALE FACTOR= 64.347 k c/s, OFFSET= 8.234 k c/s PASS ENERGY=178.950 eV Al 400 W



ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACO TIME=84.83 min

FILE: Nitest25 Ni foil treated in lab for 24 hr. As received.


SCALE FACTOR= 1.920 k c/s, OFFSET= 8.515 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA SURVEY 11/18/93 ANGLE= 15 deg ACO TIME=29.36 min

FILE: Nitest23 Ni foil untreated. as received.


SCALE FACTOR= 80.815 k c/s, OFFSET= 11.386 k c/s PASS ENERGY=178.950 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=76.05 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 3.401 k c/s, OFFSET= 9.545 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=76.05 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 3.278 k c/s, OFFSET= 10.778 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=76.05 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 3.401 k c/s, OFFSET= 9.545 k c/s PASS ENERGY=143.050 eV Al 400 W




	Shift
a Initial Energy Point	284.800
b Shifted Energy Point	284.500
c Offset	-0.300



ESCA MULTIPLEX 11/18/93 EL=C1 REG 1 ANGLE= 15 deg ACO TIME=0.84 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 5.007 k c/s, OFFSET= 37.388 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA SURVEY 11/18/93 ANGLE= 15 deg ACO TIME=29.36 min
 FILE: Nitest21 Ni wire processed in lab. as received.
 SCALE FACTOR= 12.496 k c/s, OFFSET= 1.542 k c/s PASS ENERGY=178.950 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min

FILE: Nitest20 Ni wire processed in lab. as received.

SCALE FACTOR= 0.301 k c/s, OFFSET= 2.742 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min
FILE: Nitest20 Ni wire processed in lab. as received.
SCALE FACTOR= 0.280 k c/s, OFFSET= 2.436 k c/s PASS ENERGY=143.050 eV Al 400 W




File Nit 20

	Shift
a	Initial Energy Point
b	Shifted Energy Point
c	Offset



ESCA MULTIPLEX 11/18/93 EL=C1 REG 1 ANGLE= 15 deg ACO TIME=1.67 min
FILE: Nitest20 Ni wire processed in lab. as received.
SCALE FACTOR= 1.789 k c/s, OFFSET= 8.206 k c/s PASS ENERGY=143.050 eV Al 400 W



CURSOR

2849


Counts/Sec

32758


Counts

55.100


a Energy (eV)



ESCA SURVEY 11/22/93 ANGLE= 15 deg ACO TIME=29.36 min
 FILE: Nitest33 2nd Ni wire treated prior to IRC.
 SCALE FACTOR= 11.123 k c/s, OFFSET= 1.299 k c/s PASS ENERGY=178.950 eV Al 400 W




$N(E)/E, \text{sat, Shf}$




ESCA MULTIPLEX 11/22/93 EL=C1 REC 1 ANGLE= 15 deg ACQ TIME=1.67 min
FILE: Nitest32 2nd Ni wire treated prior to IRC.
SCALE FACTOR= 1.491 k c/s, OFFSET= 5.842 k c/s PASS ENERGY=143.050 eV Al 400 H


ESCA MULTIPLEX 11/22/93 EL= REG 2 ANGLE= 15 deg ACO TIME=96.53 min
FILE: Nitest32 2nd Ni wire treated prior to IRC.
SCALE FACTOR= 0.254 k c/s, OFFSET= 1.784 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min
FILE: Nitest20 Ni wire processed in lab. as received.
SCALE FACTOR= 0.331 k c/s, OFFSET= 2.436 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACO TIME=84.83 min
FILE: Nitest25 Ni foil treated in lab for 24 hr. As received.
SCALE FACTOR= 1.920 k c/s, OFFSET= 8.515 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=76.05 min
FILE: Nitest22 Ni foil untreated. as received.
SCALE FACTOR= 3.401 k c/s, OFFSET= 9.545 k c/s PASS ENERGY=143.050 eV Al 400 W




ESCA MULTIPLEX 11/18/93 EL= REG 2 ANGLE= 15 deg ACO TIME=67.28 min
FILE: Nitest20 Ni wire processed in lab. as received.
SCALE FACTOR= 0.331 k c/s, OFFSET= 2.436 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/19/93 EL= REG 2 ANGLE= 15 deg ACQ TIME=61.43 min
FILE: Nitest27 Ni wire untreated (base line) using Al X-Ray's.
SCALE FACTOR= 0.326 k c/s, OFFSET= 1.491 k c/s PASS ENERGY=143.050 eV Al 400 W



ESCA MULTIPLEX 11/22/93 EL= REG 2 ANGLE= 15 deg ACO TIME=96.53 min
FILE: Nitest32 2nd Ni wire treated prior to IRC.
SCALE FACTOR= 0.274 k c/s, OFFSET= 1.580 k c/s PASS ENERGY=143.050 eV A1 400 W



THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)